

Highlights:

- 28 AWG thin and dense stranded conductors
- Flexible PVC jacket
- 0.30 " (Ø) outer diameter
- Oxygen free copper
- Integrated stereo audio section
- Double Al-foil shielding

Product information:

CLV115 is a high quality SVGA cable with 5 coaxial conductors carrying the RGBHV signals. A aluminium foil shielding will grant with 100% coverage. EDID and DDC are supported. The connectors are gold plated to ensure maximum connectivity. All pins are connected. On one side, the mini jack cable end is 15 cm (projector side) and on the other side (computer side) the mini jack cable end is 50 cm.



Components:

- CableType: SVGA215 - Audio + Video Cable

Properties:



Product Features:

Application	AV & IT
Series	Classic Series

Physical Characteristics:

Inner conductor	Insulation	Material		FPE 1.55 mm (Ø)
		Colours		White
Shielding		Aluminium foil		Al-mylar, 100% coverage - 25% Overlap
		Drain wire		BC 7 x 0.12 mm (Ø) (OFC)
Audio		Insulation	Material	PE 7540 0.7 mm (Ø)
			Colours	Grey / Purple
		Shielding	Spiral	CCA 28 x 0.12 mm (Ø)
Overall shielding	Aluminium foil		Al-mylar, 100% coverage - 25% Overlap	
		Drain wire		BC 7 x 0.16 mm (Ø) (OFC)
Outer jacket	Material		PVC 7.5 mm (Ø)	
		Colours		Black
Type of cable		75 Ω VGA video cable		
Inner conductor	Material		BC 7 x 0.12 mm (Ø) (OFC)	
Audio		Material		BC 10 x 0.12 mm (Ø) (OFC)
Filling		Cotton Yarn		
Inner conductor	American Wire Gauge		28 AWG	
Fitted connectors		SVGA male		

Variants:

- CLV115/1.5 - 1,5 meter
- CLV115/15 - 15 meter
- CLV115/20 - 20 meter
- CLV115/25 - 25 meter
- CLV115/30 - 30 meter

Component details:

# SVGA215

Audio + Video Cable

This cable is a cable only used as a productioncomponent for PROCAB pre-made cables and is not sold seperately or in bulk. Consult the productsheet for detailed information.