


Product information:

The PAC252 is a hybrid power/audio cable which consists of 3 x 2,5mm² power section and two times a 2 x 0.22mm² 110 Ohm signal pair. The dual signal pair makes it ideal for applications where a stereo signal is needed or where the second pair is used as redundancy. The power and the 2 signal cables each have a separate jacket which makes it easy to split out the cables at the end.

Components:


- CableType: HMX224 - 24 AWG Balanced signal / DMX-AES cable
- CableType: HPC3G2.5 - 3G2.5 3 x 2.5 mm² PVC power cable



Certification:



Properties:



Product Features:

Application	Rental & MI
Series	Bulk & Accessories

Physical Characteristics:

Components		2 x HMX224
		1 x HPC3G2.5
Outer jacket	Material	Highflex PVC 18.0 mm (Ø)
	Colours	Black
Type of cable		Power & 2 x DMX-AES 110 Ω cable
Filling		Non-woven (PET/PA) tape


Standards & regulations:

RoHS2 compliant	According EU Directive 2011/65/EU
Reach compliant	According EC 1907/2006
Flammability test	According EN 60332-1-2

Mechanical Characteristics:

Temperature range	Fixed installation	- 59 °F till + 158 °F
	Mobile installation	- 41 °F till + 167 °F
Bending radius	Fixed installation	6 x outer diameter
	Mobile installation	8 x outer diameter

Cross sections:




Variants:

- PAC252/1 - 100 meter
- PAC252/3 - 300 meter

# HMX224

## 24 AWG Balanced signal / DMX-AES cable

This cable is only used as a production component for PROCAB pre-made cables and is not sold separately or in bulk. Consult the product sheet for detailed information about this component.



### Physical Characteristics:

Inner conductor	Audio	Material		TC 7 x 0.2 mm (Ø) (OFC)
		Section		0.00034 "²
		American Wire Gauge		24 AWG
		Number of conductors		2
		Insulation	Material	PE 1.5 mm (Ø)
			Colours	Red / Blue
		Shielding	Aluminium foil	Al-mylar, 100% coverage - 25% Overlap
		Drain wire	TC 7 x 0.2 mm (Ø) (OFC)	
		Braiding	TC 7 x 16 x 0.1 mm (Ø) (OFC)	
	Filling			Non-woven (PET/PA) tape
Outer jacket	Material		PVC 5.0 mm (Ø)	
	Colours		Black	

Electrical Characteristics:

Max. conductor	DC resistance	85 (Ω / Km)
Max. shielding	DC resistance	25 (Ω / Km)
Audio		47 (pF/m)
Characteristic impedance		110 Ω ± 10% Ω
Nom. Velocity of propagation		75 %
Return loss (dB)		(From 1 to 25 mHz) > 20 dB
Dielectric strength		(Cond/Shield) 1.2 (KV / 1 min. DC)
		(Cond/Cond) 0.5 (KV / 1 min. DC)

# HPC3G2.5

3G2.5 3 x 2.5 mm² PVC power cable

This cable is only used as a production component for PROCAB pre-made cables and is not sold separately or in bulk. Consult the product sheet for detailed information about this component.



Physical Characteristics:

Inner conductor	Power	Material	BC 48 x 0.25 mm (Ø) (OFC)		
		Section	0.0039 “2		
		American Wire Gauge	16 AWG		
		Number of conductors	3		
		Insulation	Material	PVC 3.7 mm (Ø)	
			Colours	Blue / Brown / Yellow & Green	
Outer jacket	Material				PVC 10 mm (Ø)
	Colours				Black

Electrical Characteristics:

Max. conductor	DC resistance	7.98 ( $\Omega$ / Km)
Resistance	Insulation	> 200 M $\Omega$ / km
Rated voltage		Uo/U 300/500 V
Dielectric strength		2.5 (KV / 1 min. DC)